

EDI7310950



Tailored drying for the most delicate items

The 700 DelicateCare Heat Pump Dryer adjusts the temperature and motion of the drum to specific fabrics, ensuring tailored care. Silks retain their shape, woolens get safely dried with no shrinkage and water repellency of outdoor garments is restored. Woolmark certified.

Product Benefits & Features



DelicateCare - dries wool with no shrinkage guaranteed*

DelicateCare uses heat pump technology to dry delicate garments with tailored drum temperatures and movements, helping clothes last longer. Even fabrics such as silk and wool are dried with superior Care. Woolmark certified.



No sorting needed. Mixed loads each time evenly dried with MixCare

MixCare provides powerful yet gentle drying for mixed loads of cottons and synthetics, ensuring clothes are evenly dried with no sorting needed.

*Comparable with flat drying.



SensiCare – optimal drying to preserve your clothes

SensiCare measures the temperature and humidity of each load, adjusting the time and energy consumption accordingly, so garments are protected from overheating and overdrying. Clothes look and feel new for longer without wasting energy.



The Hygiene cycle removes more than 99.9% of bacteria and viruses

The Hygiene cycle runs above 60°C, drying while sanitizing items, removing 99.9% of bacteria and

- Heat pump technology achieves unprecedented energy efficiency
- DelicateCare
- · Internal light for optimal visibility in the tumble dryer
- Inverter motor technology
- · Delay start option
- Sensor dryer: the dryer senses when the clothes are dried to the level specified
- · Additional time controlled drying programs
- Program card languages: Danish, Finnish, Norwegian, Swedish
- Optional accessories: Stacking kit
- · Accessories included: Condenser Slots Brush



EDI7310950

Product Specification	
Nordic_TD_FamilyName	700 DelicateCare
Drying capacity, kg (3rd Gen)	9.0
Woolmark	Woolmark Green
Energy efficiency class, legal (E20)	С
Condensation efficiency class, (3rd gen)	В
Condensation Efficiency, % (3rd Gen)	91
Connectivity	Yes
Weighted average energy consumption / 100 cycles, kWh (E20)	106
Door hinges	Right Reversible By User
Drum volume, I	118
Porthole diameter, cm	49
Tank capacity, I	5.56
Airborne acoustical noise emissions, dBA re 1 pW	63
Airborne acoustical noise emission class	В
Dimensions HxWxD in mm	850x596x636
Depth max, mm	659
Cord length, m	1.45
Connected load, W	550
Volt, V	230

Nordic_TD_Refrigerant_Volume	R290/0.149
Frequency, Hz	50
Nordic_TD_SensiDry_or_GentleCare	GentleCare
Nordic_TD_ProSense_or_SensiCare	SensiCare
Net weight, kg	49.5
Product Number Code	916 900 450
Bar code	7333394128580